



G1"1/4 Connection(L017)

F1 F2
F3 F4



F3 F4 нагреваемая сторона: F3 вход, F4 выход

F1 F2 греющая сторона: F1 вход, F2 выход



Design pressuer(MPa)	3.0
Testing pressuer(MPa)	4.5
Design Temperature(°C)	-196~+200°C
Label Code	

FHT5433-058		100	239±5	F1F2side:3.00 ;F3F4side:2.94	10.50	2.94
FHT5433-057		90	216±3	F1F2side:2.70 ;F3F4side:2.64	9.60	2.64
FHT5433-056		80	194±3	F1F2side:2.40 ;F3F4side:2.34	8.70	2.34
FHT5433-055		70	171±3	F1F2side:2.10 ;F3F4side:2.04	7.80	2.04
FHT5433-054		60	148±3	F1F2side:1.80 ;F3F4side:1.74	6.90	1.74
FHT5433-053		50	126±3	F1F2side:1.50 ;F3F4side:1.44	6.00	1.44
FHT5433-052		40	103±2	F1F2side:1.20 ;F3F4side:1.14	5.10	1.14

Drawing No.	Customer Part No.	Plate No.	A(mm)	Volume(L)	Weight (kg)	Heat transfer area(m ²)
Connection vertical degree: ±2°						
				Plate material: 316L		
				Connection material: 304		
				Cover plate material: 304		
				SNB030B-N-3.0-H F1F2F3F4(G1"1/4)		
Mark No.	Change file No	sign	Date	View	Scale	Size
Design	XUZH	Standard				
Check		Approved				
Review		Edition	A/0			
Process		Date	20220622		1:3	

